POTAIN®
by Manitowoc

Igo M 14

Maximum capacity: 1800 kg
Maximum jib length: 22 m
Maximum load at jib nose: 600 kg
Maximum height under hook: 19 m



Remote control

Multiple transport options

SmartCom | Steering axle | Generator | Hydraulic-leveling | Top Zone

Contact your local dealer for more information, or to find your dealer go to www.manitowoccranes.com/dealers



Steering axle +/-20°

- Adjustable drawbar with three positions or fifth wheel



Hydraulic leveling

- Cylinder rod protected from site damage
- Fast, precise locking with screws and nuts



Embedded generator set

- Diesel and sound-proof
- Accessible at all times and detachable
- Easy to fill fuel tank





Multiple chassis leg positions

- Angle of departure greater than 20°
- Optimum ground clearance, more than 400 mm
- Site exit in both directions



Two slewing radii

- Nominal radius of 2,5 m, extra short radius 2 m

Permanent steel ballast

- 2 x 2450 kg
- Complete for all configurations in and out of service
- Easy to disassemble if needed

Remote controls

- Steering axle, hydraulic leveling, generator set

Limiting and indicating devices

- Electronic and electromechanic limiter
- Load limiting device controlled by dynamometric ring

© Manitowoc
03/2016
www.manitowoccranes.com